

# DISPKIT-MINI

CTC Product Display Kit with Non-Functional Parts



## Product Features

- ▶ Ten pieces of our most popular CTC Line products
- ▶ Durable, foam-lined plastic case (11.72 in. L x 8.00 in. W x 3.86 in. H)
- ▶ Allow your customers to experience the quality and durability of a wide assortment of CTC products

## Accelerometers

- |                               |                                   |
|-------------------------------|-----------------------------------|
| ▶ <b>Standard Size Sensor</b> | <i>Top Exit, 100 mV/g Cutaway</i> |
| ▶ <b>Standard Size Sensor</b> | <i>Side Exit</i>                  |
| ▶ <b>Compact Size Sensor</b>  | <i>Top Exit</i>                   |
| ▶ <b>Compact Size Sensor</b>  | <i>Triaxial</i>                   |
| ▶ <b>Mini Size Sensor</b>     | <i>Top Exit</i>                   |

## Cables & Connectors

### ▶ CB111-V2N

CB111 Cable	<i>Twisted, Shielded Pair Cable, Yellow FEP Jacket, 0.19 in. (4.8 mm) OD, 392 °F (200 °C) Max Temp</i>
V2N Connector	<i>2 Socket MIL-Style, Seal-Tight Viton® Boot Connector with Nylon Insert, Permanent Mount, 250 °F (121 °C) Max Temp</i>

### ▶ CB206-A2A

CB206 Cable	<i>Low Cost, Twisted, Shielded Pair Cable, Lightweight Red FEP Jacket with Stainless Steel Outer Armor, 0.27 in. (6.9 mm) OD, 392 °F (200 °C) Max Temp</i>
A2A Connector	<i>2 Socket MIL-Style, Polycarbonate Molded Connector, Permanent Mount, 250 °F (121 °C) Max Temp</i>

## Mounting Hardware

- |                   |   |
|-------------------|---|
| ▶ <b>MH103-1B</b> | <i>Flat Surface Magnet Mounting Base with 1/4-28 Integral Mounting Stud, 40 lbs. (18 kg) Pull Strength, 1.00 in. (25.4 mm) OD, 0.46 in. (11.68 mm) Height</i> |
| ▶ <b>MH130-1A</b> | <i>Adhesive Mounting Disk with 1/4-28 Blind Tapped Hole, 1.00 in. (25.4 mm) Diameter</i>  |
| ▶ <b>MH118-3A</b> | <i>Motor Fin Mount Probe Pad, 0.25 in. x 1.75 in. (6.35 mm x 44.45 mm) Probe Tip</i>  |